

Claris Pro and FileMaker Pro HelpReference > [Functions reference](#) > [Get functions](#) > Get(LastErrorDetail)

Get(LastErrorDetail)

Returns text about errors that are returned by Get(LastError).

Format

Get (LastErrorDetail)

Parameters

None

Data type returned

text

Originated in version

6.0 or earlier

Description

- For ODBC imports and Execute SQL script steps, returns a detailed ODBC error message.
- For working with ODBC data sources in the relationships graph, returns the readable error string that is generated by the ODBC driver.
- For actions that attempt to connect to a host securely, returns an SSL certificate error message.
- For external script steps, returns an error message if it is specified by the plug-in.
- For operations that use cURL options, returns a message from the cURL library or a response code from the server. See [Supported cURL options](#).
- For operations that attempt to lock records already in use, returns the name and account of the user currently editing the record.
- For plug-ins that fail to install or load, returns an error message.
- For transactions that fail or revert, returns the failing script, the failing script step, and the script line number. If the failure occurs in a subscript, the subscript name is given instead of the calling script name. See [Open Transaction](#).

Example 1

For ODBC imports and Execute SQL script steps, returns **[DataDirect][Macintosh ODBC Driver Manager] Data source name not found and no default driver specified (-1)** when a data source name wasn't found and the driver wasn't specified.

Related topics

[Functions reference](#)

[About formulas](#)

[About functions](#)

[Defining calculation fields](#)

[Using operators in formulas](#)

[Editing ODBC data sources](#)

Was this topic helpful? [Send feedback](#)